

Solar mobile ice maker configurations

STITY SURV S MOTY			
	Normal Solar pan		
Parameters	Symbol	SDPV-100WpS	Pic
Maximum power	Pm	100W	-
Open Circuil voltage	Voc	22.2V	
Maximum power voltage	Vmp	24V	
Short circuit current Maximum power current	lsc Imp	3.02A 2.84A	
Module efficiency		16%	
Series fuse rating	ηm16% 15Α		
Size	485*670*25mm		
Weight:	2.5k		
	conditions SCT:1,000/m2,AM1.5,temp		
Fully Charge time		wer bank of 500Wh, it will take 10 h	nrs under sun
	Foldable solar par	nel(Option 2)	
Parameters	Symbol	SDPF-80W	
Maximum power	Pm	80W	
Working voltage	V	18-25V	
Open Size	cm	109*30cm	
Close size	cm	18*30cm	
Weight	Kg	1	
Efficiency	ηm	22%	
Blac	k 600D with PVC coating fabric materi	ial	
Fully Charge time	to charge the por	wer bank of 500Wh, it will take 12 h	nrs under sun
	Multi functional powe	r bank SD-500W	
Out put	12Vdc/8.0A(max)		
Battery type and capacity	Lithium battery 14.8V/36Ah		
Case size	381.3*243*128mm		
Net weight	7.5Kg		
Cycle times of the battery	≥800 times(more than 80% capacity)		
Working temperature	_10~65°C		
Altitute	below 2000m		
Self Protection function	short -circuit protection, over current protection, over temp protection, ov		er voltage protection,over charg
Performance fully charged	8hrs	protection 7hrs	5.5hrs
(working time against the model)	SDZB-12	SDZB-20	SDZB-55
DC Voltage Input	DC12/24V(Optional) solar system	DC12/24 V(Optional)	DC24 36V(Optional)
		· · · ·	
AC Voltage Input	AC110~240V(by adaptor)	AC110~240V()	AC110~240V()
Average Power	60~90W	70~90W	90~130W
ce Making Capacity	10~15KG/24hours	15~20KG/24hours	45~55KG/24hours
ce Storage Capacity	0.7KG	1.2KG	15KG
Ice of a cycle	9 pcs	24 pcs	45 pcs
Performance	9 tube ice every 8 10 minutes	24 tube ice every 15 20 minutes	45 tube ice every 15 20 minute

Ice shape	Cylindrical bullet	Cubic	Cubic
Climate	N/SN/ST	N/SN/ST	N/SN/ST
Refrigerant	R134a/R600a	R134a/R600a	R134a/R600a
Net Weight(KG)	9Kg	12	28
Gross Weight(KG)	10Kg	13	31
Product size(WxDxH)mm	242x358x328	287x375x357	448x400x793
Packing size(WxDxH)mm	288x380x376	331x422x420	500x460x850
Loading Quantity(20'/40'/40HQ)	732/1512/1764PCS	470/970/1164PCS	114/244/366PCS
Features and pictures: 1.Using high efficiency DC compressor,super power saving 3.Low voltage / Over voltage protection 4.Wide working voltage range 5.Intelligent operation and timing 6.Full-closed structure to ensure the			